

7000 SERIES HEAVY DUTY

CONCEALED MOUNT

7000 HDCM



SPECIFICATIONS

Applications	<ul style="list-style-type: none">• 7015C- Concealed friction• 7016C- Concealed stop only• 7017C- Concealed hold open
Box Quantity	1
Case Quantity	6
Certifications	<ul style="list-style-type: none">• BHMA and ANSI156.8 Compliant• UL/cUL Listed for up to 3 hours (stop only)• UL10C Positive Pressure Rated (stop only)• UL10B Neutral Pressure Rated (stop only)
Door Thickness	<ul style="list-style-type: none">• 1-3/4" (44 mm) thick door - standard• 1-3/8" - 2-1/4" (36 mm - 57 mm) thick door - optional
Fasteners	Standard screw packet included for wood or metal door and frame applications
Finishes	<ul style="list-style-type: none">• US10B, US32D (for stainless steel)
Handing	Non-handed
Material	Steel, stainless steel
Mounting Style	Concealed
Notes	<ul style="list-style-type: none">• Adjustable arms provide easy installation• Slide track design• Adjustable in the field• Heavy shock absorber spring provides 5° to 7° compression before dead stop• Special templating upon request• Single and double acting doors• Degree of opening is fully adjustable and can be adapted to changing needs between 85° to 110°• Not recommended for exterior use or for use with aluminum doors
Product Description	Heavy Duty Concealed Mount

By clicking 'Accept All' you consent that we may collect information about you for various purposes, including: Functionality, Statistics and Marketing

[customize settings](#)

ACCEPT ALL

DECLINE ALL

By clicking 'Accept All' you consent that we may collect information about you for various purposes, including: Functionality, Statistics and Marketing